




GOOD DISTRIBUTION PRACTICES SYSTEMS
for the Pharmaceutical / Biotechnology Industry

Datalogger -40°C to +85°C

XpertLog® GDP





Docking station



Temperature



Humidity



XpertLog® GDP

covers all the applications between -40 to 85°C
offers the best accuracy in its class: +/- 0.1°C
user friendly
data integrity - FDA 21 CFR Part 11 compliant

+ Network ready: multiple users may simultaneously share the same database

Technical specifications:

Suitable applications:

Refrigerators
Cold rooms
Warehouses

Logger type

Temperature

Humidity

Sensor Type

- flexible
 - rigid
 - customized
- Range
Accuracy

4 wires PT-100
PTFE 19"(480mm)
1"(25mm) / 6"(150mm)
-40°C to +85°C
± 0.1°C

4 wires PT-100
capacitive
1"(25mm)
PTFE 19"(480mm)
15% to 95% RH
± 0.1°C
± 2.0%RH @ 23°C (15 - 95% RH)

- Weight
Battery
Diameter
Height
Sampling rate
Memory capacity
Battery lifetime
Internal clock drift
Docking station

20 g
lithium, user replaceable
40 mm
27 mm
1 sec to 24 hours
32,000
up to 10 month - based on user usage
4 sec / 24 hours @ 23°C
USB to computer
Available models: 4, 8, 12 and 20 ports

50 g
lithium, user replaceable
40 mm
35 mm
1 sec to 24 hours
16,000rh / 16,000 temp.

- Material
Enclosure
Calibrations

FDA compliant
IP67
Factory traceable NIST / COFRAC - ITS-90 coefficients resides in the internal memory



U.S.A.
99, Pine Hill Rd
Nashua, NH 03063
Ph: + 1 603-821-1898
Fax: + 1 603-821-1888

Canada
1751 rue Richardson,
suite 8207,
Montreal, Qc, H3K 1G6

China
1511, Building B,
No.15 Changyi Road,
Shanghai: 200439
P.R. CHINA
Ph: +86-21-6687-7897

France
3, rue Jules Guesde
92300 Levallois Perret
Ph: + 33 142-708-589
Fax: + 33 142-708-744

Romania
Blv. Industriei nr. 7
300714 Timisoara, jud. Timis
Ph: + 40 722 247 887
+ 40 726 709 632
Fax: + 40 256 222 415